

# RCA-PDA001-09



Tripod or Clip holder

## MATERIALS

### CASE

- Fiber Reinforced Plastic case
- Water Proof Case
- Water based paint

### STAND, WIRE, & CONNECTOR

- Aluminum tripod or Clip
- Gold Plated Copper Connector
- Low Loss RF Copper cable

## SPECIFICATION

■ FREQUENCY:	2.4		<b>Ghz</b>
■ BEAMWIDTH:	38	elevation	<b>Degree</b>
■ BEAMWIDTH:	45	azimuth	<b>Degree</b>
■ GAIN:	9		<b>dB</b>
■ POLARITY:		Hor / Ver	
■ FRONT TO BACK RATIO	22		<b>dB</b>
■ WIND LOAD:	N.A.		<b>Lbs</b>
■ WIND LOAD:	N.A.		<b>Lbs</b>
■ SIZE:	50 X 60	panel	<b>mm</b>
■ HEIGHT:	90	with tripod	<b>mm</b>
■ WEIGHT:	1		<b>Lb</b>
■ CONNECTOR:	Reverse female SMA		
■ CABLE LENGTH**:	1.5		<b>Meters</b>
■ CABLE LOSS:	0.2		<b>dB/meter</b>
■ TILT ANGLE:	280		<b>Degree</b>

\*\* For special request please indicate in the form additional charge will be applied

*This document and the information contained is property of Roughclaw Enterprise. Unauthorized copying is not allowed. The information in this document is believed to be correct at the time of writing. Roughclaw Enterprise reserves the right at any time to change said content, circuitry and specifications.*